

JS055

CLEANER FOR MIXERS

TREMCO
Lasting Performance



KEY BENEFITS SUMMARY

- No chlorinated hydrocarbon
- Low evaporation rate
- Facilitates the cleaning of mixers
- Promotes the removal of cured sealant

PRODUCT INFORMATION

Description

- JS055 is used in mixing equipment cleaning operations.
- It is particularly suitable for cleaning elements that are in contact with two-component polyurethane sealants.

Packaging

18 kg pail

Storage

In dry conditions between +5°C and +25°C

Shelf life

In original unopened packaging:
36 months

Implementation

- JS055 is used neat (undiluted) in the rinsing pumps (circulation) or in static cleaning baths.
- Some ABS, silicone, rubber and polystyrene components and other plastics may be damaged on contact with the product.
- Use polyethylene, polypropylene or PTFE hoses and seals.

Safety precautions

The Technical and Safety Data Sheets must be read and understood before use.

Service

Our team of technicians remains at your disposal for any further information.

TECHNICAL DATA

CHARACTERISTICS	VALUES
Appearance	Liquid
Color	Colorless to light yellow
Density*	0.91
Flash point	> 62°C

*Typical values

Note

The information in this document is provided for informational purposes and are non-binding. Technical data are not expressly warranted characteristics of the goods.

Because the variety of material used, the variety of application processes and the variety of conditions of use are beyond our control, preliminary tests are strongly recommended before any order.

The information and illustrations being reproduced on this document are based on features in progress and on our experience at the time of May 2015.

The manufacturer reserves the right of modifying the technical characteristics of its products at any time.

The warranty policy of these products is exclusively governed by our general terms and conditions of sales. tremco illbruck can not be held liable based on the general information given by this document.

