

# DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

**TREMCO**  
Lasting Performance

No. SX100 – 20180215

1. **Unique identification code of the product-type:** SX100
2. **Intended use/es:** Cement screed material for use internally in buildings – EN 13813:2002
3. **Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
5. **System/s of AVCP:** System 4 (for internal uses)
- 6a. **Harmonised standard:** EN 13813:2002 (CT-C30-F8)

**Notified body/ies:** Not relevant

7. **Declared performance/s:**


EN 13813:2002 (Cement screed material for use internally in buildings (wearing surfaces))

Essential Characteristic	Performance	Harmonised Technical Specification
Release of corrosive substances	CT	EN 13813:2002
Compressive strength	C30	EN 13813:2002
Flexural strength	F8	EN 13813:2002
Reaction to fire	BFL –s1	EN 13813:2002
Water Permeability	NPD	EN 13813:2002

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**

M. Liptrot, Business Unit Director Sealants & Coatings  
At Wigan on 15 February 2018



**Annex:**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

**TREMCO**

<b>CE</b>	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 18 SX100 – 20180215 tremco-europe.com/SX100/	
EN 13813:2002 Cement screed material for use internally in buildings (non-wearing surfaces)	
<b>Essential Characteristic</b>	<b>Performance</b>
Release of corrosive substances	CT
Compressive strength	C30
Flexural strength	F8
Reaction to Fire	BFL –s1
Water Permeability	NPD