

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **TREMCO CP215**

· MSDS code: W-T-CP215

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Resin

Binder

Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Contains:

methyl methacrylate

2-ethylhexyl acrylate

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 1)

Triethylene glycol dimethacrylate

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-xxxx	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	30- <50%
CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453158-37-xxxx	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	20- <30%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21-xxxx	Triethylene glycol dimethacrylate Skin Sens. 1, H317	1- <5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Remove from the skin using a cloth or paper. Then clean with water and soap.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Irritating to respiratory system.
Irritant to skin and mucous membranes.
Allergic reactions
- **Information for doctor:** No further relevant information available.
- **Hazards** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Fumes can combine with air to form an explosive mixture.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Remove persons from danger area.
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Use only in well-ventilated areas.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 3)

Do not breathe vapour.

Open and handle receptacle with care.

Keep away from heat and direct sunlight.

Avoid contact with the eyes and skin.

- **Information about fire - and explosion protection:**

Highly flammable.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

- **Information about storage in one common storage facility:**

Store away from oxidising agents.

Store away from foodstuffs.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Storage temperature: +5 °C to +25 °C

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	------------------------------------------------------------------------------------------------------

- **Additional information:**

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

- **Respiratory protection:**

Use only in well-ventilated areas.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 4)

- **Protection of hands:**



Protective gloves

- **Material of gloves**

Butyl rubber, BR

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Colourless

- **Odour:** Strong

- **Odour threshold:** 0.05 ppm (CAS 80-62-6)

- **Melting point/freezing point:** -48 °C

- **Initial boiling point and boiling range:** 100 °C (CAS 80-62-6)

- **Flash point:** 11 °C (CAS 80-62-6)

- **Ignition temperature:** 430 °C (CAS 80-62-6)

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: 2.1 Vol % (CAS 80-62-6)

Upper: 12.5 Vol % (CAS 80-62-6)

- **Vapour pressure at 20 °C:** 38.7 mBar (CAS 80-62-6)

- **Density at 20 °C:** 0.99 g/cm³

- **Solubility in / Miscibility with water at 20 °C:** 15.9 g/l (CAS 80-62-6)

- **Partition coefficient: n-octanol/water:** 1.38 log POW (CAS 80-62-6)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 5)

- | | |
|--------------------------------|--------------------------------------------|
| · Viscosity: | |
| Dynamic at 20 °C: | 160 - 200 mPas |
| · Solvent content: | |
| VOC (EU) | Not applicable. |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with heavy metals.
Reacts with acids, alkalis and oxidising agents.
Reacts with amines.
Reacts with peroxides and other radical forming substances.
Exothermic polymerisation.
- **10.4 Conditions to avoid**
Water / moisture.
Keep away from heat.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Irritating to eyes.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** Moderately / partly biodegradable

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 6)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Disposal must be made according to official regulations.
Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.
- **Waste disposal key:** UK (WM3) : HP3 HP4 HP5 HP13

· European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- **Uncleaned packaging:**
- **Recommendation:**
Dispose of packaging according to regulations on the disposal of packagings.
Non contaminated packagings may be recycled.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, ADN, IMDG, IATA** UN1866
- **14.2 UN proper shipping name**
- **ADR** 1866 RESIN SOLUTION
- **IMDG, IATA** RESIN SOLUTION

· 14.3 Transport hazard class(es)

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 7)

· ADN/R Class:	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	
· Danger code (Kemler):	Warning: Flammable liquids.
· EMS Number:	339
· Stowage Category	F-E,S-D
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION MIXTURE, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).
 - "REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).
 - COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.03.2017

Version number 3

Revision: 13.03.2017

Trade name: TREMCO CP215

(Contd. of page 8)

- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**