

CP600

REINFORCEMENT BAND

KEY BENEFITS SUMMARY

- An effective method for detailing critical waterproof transitions
- Compatible with CP250 waterproofing systems
- Provides additional waterproofing in high risk areas

PRODUCT INFORMATION

Description

CP600 is a reinforcement flashing that consists of a central strip of SEBS rubber flanked on either side by an absorbent non-woven felt.

Uses

CP600 is used as a flashing material at joints, at transitions in plane, at horizontal-to-vertical transitions and any other situation in waterproofing where a durable, reinforcing sheeting is required.

Packaging

240 mm x 30 m rolls

Colour

Grey

Availability

Direct from tremco illbruck (see bottom of leaflet for address and telephone details).

Method of Application

Refer to project-specific instructions for details of application procedures. Contact Tremco illbruck for full details.

Health & Safety Precaution

Safety data sheet must be read and understood before use.

Health & Safety Precaution

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Storage	Store in shaded dry conditions between +5°C and +25°C
Shelf Life	24 months when stored as recommended in original unopened containers

