

CP620

HEAVY DUTY PROTECTION COURSE

KEY BENEFITS SUMMARY

- Excellent membrane protection
- Light weight
- Ease of installation
- High strength and puncture resistance
- Resistant to ultraviolet degradation

PRODUCT INFORMATION

Description

CP620 is a reinforced modified bitumen protection course for waterproof membranes.

Usage / Purpose

CP620 is used as a strong protection course for protection over CP250 or other waterproofing membranes. The system can be installed within minutes over a cured membrane to give maximum protection against backfill, poured slabs and other trades.

LIMITATIONS

Not intended for use in fully immersed conditions. Not to be exposed to solvents, oils, or other contaminants harmful to asphaltic materials.

Colour

Black

Packaging

1 m wide x 20 m roll

Availability

Direct from tremco illbruck (see bottom of leaflet for address and telephone details).

Method of Application

When installing over cold fluid-applied membranes, allow the membrane to cure completely before laying CP620. Allow a 10 cm overlap between sheets.

Health & Safety Precaution

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Composition	SBS modified bitumen sheet
Storage	Store in shaded dry conditions between +5°C and +27°C
Shelf Life	12 months when stored as recommended in original unopened containers

