

CP951

URETHANE SEALER



KEY BENEFITS SUMMARY

- Can be applied over existing polyurethane coatings - ideal for refurbishment applications
- Rapid curing - can be trafficked in as little as 24 hours (refer to technical data table)
- Extremely tough coating with excellent abrasion and chemical resistance

PRODUCT INFORMATION

Description

CP951 is a high-performance, two-part polyurethane waterproofing and wearing coating for vehicular and pedestrian applications where low odour and extremely durable coatings are required.

Uses

CP951 is ideal for the fast-track refurbishment of concrete decks:

- can be applied over existing PU deck coatings without the need to remove the existing system.
- accepts pedestrian traffic within 24 hours of application, minimising down time.

CP951 can also be used as part of a TREMCO CP Urethane Waterproofing System.

Packaging

Part A: 14 litres
Part B: 3.5 litres

Colour

Clear
The TREMCO range of colour pastes may be added to provide the desired colour – please contact for details.

Availability

Direct from tremco illbruck (see bottom of leaflet for address and telephone details).

Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Method of Application

Refer to project-specific instructions for details of application procedures. Contact tremco illbruck for full details.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

CP951

URETHANE SEALER

TREMCO

TECHNICAL DATA

PROPERTY	RESULT
Composition	CP951 is a high performance 2-part polyurethane coating based on advanced PU technology
Specific Gravity	1.20
Pot Life (@ +20°C)	6 hours
Maximum Tensile Stress	35 MPa
Elongation at Break	260%
Traffic Times	Pedestrian traffic: 24 hours Vehicular traffic: 5 days minimum
Coverage	Application rates vary depending on substrate conditions
Storage	Store in dry, shaded conditions between +5°C and +25°C
Shelf Life	24 months when stored as recommended in original unopened containers



tremco illbruck Limited, Coupland Rd,
Hindley Green, Wigan, WN2 4HT, UK.
Tel: +44 (0)1942 251400
Fax: +44 (0)1942 251410
Email: uk.info@tremco-illbruck.com
Website: www.tremco-illbruck.co.uk


www.tremco-illbruck.com

2017-09 v03