

# CP135 AlphaGuard® WB Primer

## QUICK DRYING, WATER-BASED PRIMER



### KEY BENEFITS SUMMARY

- Adhesion Promoter
  - Conditions a variety of roofing substrates
- Quick Drying
  - Minimises wait time for curing
- Water Based
  - Environmentally cleaner
  - Low odour

### PRODUCT INFORMATION

#### Description

CP135 is a water-based, polymer modified primer which conditions a variety of roofing substrates prior to the application of AlphaGuard systems.

#### Usage / Purpose

CP135 promotes adhesion for the AlphaGuard Coating System to new and aged bitumen based or single ply membranes. A trial/test area must be performed prior to project approval.

#### Packaging

Available in 18.9 litre containers.

#### Colour

Milky white

#### Availability

Direct from tremco illbruck (see bottom of leaflet for address and telephone details).

#### Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

#### Application Method

- Brush or roller

#### Mixing

- DO NOT USE A HEAVY DUTY POWER DRILL. Use a standard drill with Jiffy Mixer attachment.

#### Application

- Surface must be clean and dry before applying. CP135 is milky white in the container and when first applied, but will dry to a clear finish.
- Apply primer to completely dry substrates and allow the primer to completely dry prior to applying AlphaGuard BIO System.
- Keep foot traffic to a minimum on primed surfaces.
- Re-prime as required.

#### Please Note

- Surface must be free of dirt, oils and other contaminants which would inhibit good adhesion.
- Not intended to be used as a final coating.
- Application temperature must be 10°C and rising.
- Do not apply when rain is imminent.
- Do not allow material to freeze.
- Surfaces primed with CP135 must be re-primed if allowed to remain open for more than 24 hours.

#### Health & Safety Precautions

Safety data sheet must be read and understood before use.

#### Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

#### Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge. No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

# CP135 AlphaGuard® WB Primer

QUICK DRYING, WATER-BASED PRIMER

**TREMCO**

## TECHNICAL DATA

PROPERTY	RESULT
Composition	Water-based polymer
Density (25°C) ASTM D 1475-90	0.94g/cm <sup>3</sup>
Asbestos Content (ASTM D 276-87)	None
Coverage	Coverage will vary depending upon surface porosity and application conditions. Approximately 5 - 6 m <sup>2</sup> /l for smooth surfaces. Granule surfaced MB: 1.7 - 2.5 m <sup>2</sup> /l).
Storage	Store in dry shaded conditions between +15°C and +26°C and low humidity. Storage temperatures must not exceed 43°C. Do not store in direct sunlight.
Shelf Life	12 months when stored as recommended in original unopened packaging



tremco illbruck Limited, Coupland Rd,  
Hindley Green, Wigan, WN2 4HT, UK.  
Tel: +44 (0)1942 251400  
Fax: +44 (0)1942 251410  
Email: [uk.info@tremco-illbruck.com](mailto:uk.info@tremco-illbruck.com)  
Website: [www.tremco-illbruck.co.uk](http://www.tremco-illbruck.co.uk)



[www.tremco-illbruck.com](http://www.tremco-illbruck.com)

2019-02